

Since 1999

## Flow" Full Size 6 Pan Convection Oven

(Oven/Proofer Combination)







## Model HSM-6

## "Counter-Model"

#### Oven Features:

- Unique Design Insures Even Baking 6 Pan Capacity
- · Lifeline Hinges / Positive Closure
- 2-Speed Fan
- · Field Reversible Full-View Heat Reflective Glass Door - Fully Gasketed
- Solid State Thermostat 100° 450°
- Solid State Digital Timer With 2 Memories
- Stainless Steel Interior & Exterior
- 4" Adjustable Spacing

(\*\* Check local codes)

No Venting Required In Most Areas\*\*

## Model HSM-6/P-8S

### "Oven/Proofer Combination"

#### Proofer Features:

- · 8 Pan Capacity
- Individual Heat and Humidity Controls
- Circulating Blower
- Visible Humidity Pan-Trouble-Free
- 60 Minute Electro-Mechanical Timer
- Lifeline Hinges / Positive Closure
- Stainless Steel Interior & Exterior

#### Options:

Oven: Internal Steam or Steam Generator Proofer: Auto-Fill Humidity Pan

## Model HSM-6/CRB "Cooling Rack Base"

### Cooling Rack Base:

- 7 Pan Capacity
- 4" Adjustable Spacing
- 4" Casters
- Stainless Steel Overall
- · Open Front and Back for Flow-Through Cooling





MADE IN USA

# **SPECIFICATIONS**

#### **Dimensions**

HSM-6 (Oven Only)

Exterior: 31-1/2" Width

34" Depth 39" Height

Interior:

19" Width

28" Depth 28" Height

HSM-6 / P-8S (Oven-Proofer)

Overall Exterior:

31-1/2" Width 34" Depth

79" Height (On 4" costers)


Proofer Interior:


19" Width

29" Depth

27" Height







MODEL HSM 6/P-8S

HSM-6/CRB (Oven-Cooling Rack) Overall Exterior:

31-1/2" Width

34" Depth

77" Height (On 4" casters)

# **ELECTRICAL**

HSM-6 (Oven Only): 8200 watts • 9 kw • 50/60 Hz

P-8S (Proofer): 1550 watts • 50/60 Hz

MODEL#	VOLTAGE AND PHASE	NEUTRAL	TOTAL LOAD (AMPS)
HSM-6 Oven	120/208-1-50/60	REQUIRED	39.5
	120/208-3-50/60	REQUIRED	27.0
	120/240-1-50/60	REQUIRED	34.0
	120/240-3-50/60	REQUIRED	23.0
P-8S Proofer	120/1-50/60	REQUIRED	15.0

<sup>\*\*</sup> Please Specify Electrical Requirements When Ordering

## WARRANTY

One Full Year on all parts from date of purchase.

For general sales and engineering information only. All units are subject to change without notice. Please consult factory for certified specifications.

"Even Flow" Full Size Convection Oven

(Oven/Proofer Combination)

Shipping WT.: Approximately 400 lbs. Oven Only 500 lbs. Oven/Proofer 130 lbs. CR-Base



10/97

